

Technical Data: Side Arm Staplers

Model	Version	Power Source	Air pressure	Useful height mm *	Throat depth mm	For Staples
ST Q 270	Single head	food operated	-	920	345	MG ® 108,110,112,115,118,
ST Q 270 D	Twin head	food operated	-	880	345	MG ® 108,110,112,115,118,
ST L 270	Single head	food operated	-	920	345	MG ® 108,110,112,115,118,
ST Q 323	Single head	food operated	-	830	350	MG ® 312, 315, 320, 323
ST Q 520	Single head	food operated	-	830	350	MG ® 515, MG ® 520 2/0
ST Q 523	Single head	food operated	-	830	350	MG ® 520 2/4, MG® 523
ST Q 535	Single head	food operated	-	810	350	MG ® + M 530, 535
ST QE 270 P	Single head	pneumatic	4-6 bar	930	350	MG ® 108,110,112,115,118,
ST QE 270 DP	Twin head	pneumatic	4-6 bar	930	350	MG ® 108,110,112,115,118,
ST LE 270 P	Single head	pneumatic	4-6 bar	930	350	MG ® 108,110,112,115,118,
ST LE 270 P/600	Single head	pneumatic	4-6 bar	930	600	MG ® 108,110,112,115,118,
ST QE 323 P	Single head	pneumatic	4-6 bar	860	330	MG ® 312, 315, 320 + 323
ST QE 520 P	Single head	pneumatic	4-6 bar	860	330	MG ® 515, MG ® 520 2/0
ST QE 523 P	Single head	pneumatic	4-6 bar	860	330	MG ® 520 27 2/4, MG ® 523
ST QE 535 P	Single head	pneumatic	4-6 bar	850	350	MG ® + M 530, 535

in boldface = Standard Staplers, available from stock

Twin head: staple clearance 70 mm; (special versions with 50, 90 mm)

*All staplers available with higher column (100, 200, 300 or 400 mm)

Side arm staplers will be delivered with anvil for penetrating stitch, but can be fitted upon request with a reversible anvil WA for blind stitch.

Staples MG® 108 - 120;

crown size 20 mm, wire width 1,1 mm

Staples MG® 312 - 323;

crown size 36 mm, wire width 1,5 mm

Staples MG® 515 - 520 2/0;

crown size 36 mm, wire width 2,0 mm

Staples MG® 520 2/4 - 535;

crown size 36 mm, wire width 2,4 mm

